

GLOBAL ESD

SPECIFICATION

Material Type	Technical Fabrics	Weight	410 g/m ²
Supplier	Bogesunds	Durability	> 50,000 turns Martindale
Pattern	Melange	Lightfastness	6 (Scale 1-8)
Composition	90% wool, 10% Bekitex		

ABOUT

Global ESD is a top-quality dual-shaft weave with fibres that can dissipate static electricity, making it a good choice in extreme computing environments. Our 6000/8000 task chairs and our Zonit screen wall in the ESD finish are approved in line with the 2472 SP method for effective dissipation of static electricity.

Technical fabric - antistatic

COLOURS IN THE GLOBAL ESD SERIES



Global ESD

GLOBAL ESD

GLOBAL ESD FULFILLS THE FOLLOWING STANDARDS:

- | | | | |
|---|------------------------------------|------------------------------------|-------------------------------------|
| ✓ EN ISO 12947-2 + AC 12
KPA
EN ISO 12947-2+AC 12 KPa | ✓ EN ISO 12945-2
EN ISO 12945-2 | ✓ EN ISO 105-B02
EN ISO 105-B02 | ✓ EN ISO 13936-2
EN ISO 13936-2 |
| ✓ EN ISO 105-X12
EN ISO 105-X12 | ✓ EN ISO 105-D02
EN ISO 105-D02 | ✓ EN ISO 105-D01
EN ISO 105-D01 | ✓ ISO ISO 105-C06
EN ISO 105-C06 |
| ✓ ISO ISO 105-E16
EN ISO 105-E16 | ✓ EN ISO 105-E04
EN ISO 105-E04 | ✓ EN 1021-1:2014
EN 1021-1:2014 | ✓ EN 1021-2:2014
EN 1021-2:2014 |